



LEICA ERI

Technical Data



Rifle Scope	LEICA ERI 2.5-10 x 42		LEICA ERI 3-12 x 50	
Order no. Reticle	55 020	4a	56 020	4a
	55 021	4a with track	56 021	4a with track
	55 022	4a with ASV	56 022	4a with ASV
	55 023	4a with ASV and track	56 023	4a with ASV and track
	55 010	Ballistic	56 010	Ballistic
	55 011	Ballistic with track	56 011	Ballistic with track
Package includes	riflescope caps for front lens and eyepiece, cleaning tissue, battery		riflescope caps for front lens and eyepiece, cleaning tissue, battery	
Front lens diameter	42 mm		50 mm	
Magnification	2.5 - 10 x		3 - 12 x	
Zoom	4 x		4 x	
Field of view at max. magnification (m/100 m)	3.9 m/12.80 ft		3.2 m/10.50 ft	
Field of view at min. magnification (m/100 m)	14.5 m/47.57 ft		11.5 m/37.7 ft	
Eye Relief	3.94"/100 mm		3.94"/100 mm	
Exit pupil	4.2 - 14 mm		4.1 - 14 mm	
Parallax	100 m/328.08 ft		100 m/328.08 ft	
Dioptre compensation	- 4/+3 dpt.		- 4/+3 dpt.	
Coating	Aqua Dura™ lens coating		Aqua Dura™ lens coating	
Transmission	TD/TN ≥ 90 %		TD/TN ≥ 90 %	
Mounting option	30 mm tube/Zeiss internal track		30 mm tube/Zeiss internal track	
Impact point correction	1 click = 1 cm /100 m (≈ 1/3 MOA), 180 x180 cm		1 click = 1 cm /100 m (≈ 1/3 MOA), 120 x120 cm	
Front lens filter thread	M 46 x 0.75 mm		M 52 x 0.75 mm	
Length	324 mm		340 mm	
Weight	520 g (without track) / 550 g (with track)		620 g (without track) / 660 g (with track)	
Waterproof	waterproof to 4 m/13.12 ft, nitrogen-filled		waterproof to 4 m/13.12 ft, nitrogen-filled	
Available reticles	4a, Ballistic, IBS		4a, Ballistic	
Reticle illumination	yes, dot, suitable for twilight use		yes, dot, suitable for twilight use	
Automatic switch-off	3 min, ± 70°		3 min, ± 70°	
Automatic switch-on	yes, activated by position and/or movement		yes, activated by position and/or movement	
Battery	1 x CR 2032		1 x CR 2032	
Accessories	59 000	sunshade	-	