



LEICA DUOVID 10 + 15 x 50

Technical Data



Binocular	LEICA DUOVID 10 + 15 x 50
Order No. Product	
Rubber armored, black	40 420
Delivery scope	Neoprene carrying strap, contoured, eyepiece cover, Nappa leather case, Tripod adapter
Magnification	10 x/15 x
Front lens diameter	50 mm
Exit pupil	5 mm/3.3 mm
Twilight factor	22.4/27.4
Field of view at 1,000 m	92 m/70 m
Field of view at 1,000 yds	274 ft/208 ft
Eye-relief	14.5 mm
Objective angle of view	5.3°/4°
Close focusing distance	approx. 3.8 m/12.9 ft
Diopter compensation	± 3 diopters
Automatic diopter compensation ADC™	yes
Eyepieces for eyeglass wearers	yes
Adjustable interpupillary distance	59–74 mm
Sliding Eyecups	yes, removable, with two click stops
Focusing	Internal focusing via central focusing device
No. of lens elements (each side)	11, all with HDC™ coating
Prism system	Roof prism with phase correcting coating P40 and HighLux-System HLS™
Watertightness	Watertight to a depth of 5 m/16.5 ft
Housing	Die-cast aluminum, nitrogen-filled
Dimensions (W x H x D)	126 x 195 x 67 mm 4 ⁹ / ₂ x 7 ⁷ / ₁₆ x 2 ² / ₃₂ in
Weight	approx. 1,250 g / 44 oz
Order No. Accessories	
Neoprene carrying strap, contoured	included
Tripod adapter	included